

VP2225 industrial luminaire

Standard:	230V 50Hz	4000K CRI ≥70	IP65	RAL 9003	3 x 1,5 mm ²	-O-			
Options:									

The VP2225 LED luminaire is suitable for lighting of canopies, industrial halls, warehouses, and cold stores, etc. Over the years VP2225 has also been optimised for machine vision solutions.

VP2225 can be surface-mounted onto a ceiling or a lighting rail. The luminaires are equipped with Phoenix Contact IPD quick connectors for serial wiring and connection. The included fastening bracket allows changing the installation angle of the luminaire.

The VP2225 luminaire has also several intelligent lighting options, and can be equipped with Zhaga socket for wireless control.



VP2225	145W
Max. input power (W)	145
Useful quantity of light (lm)	15 000
Power ratio	According to standard EN 61000-3-2
Operating temperature (°C)	-40...+50
Measurements, l x w x h (mm)	1145 x 132 x 90
Materials	Metalwork painted aluminium and stainless steel
Fastening	Luminaire fastened to a bracket / Screw fastening for the bracket
LED lumen maintenance	Typically less than 10%/100 000 h

Lumous lighting Oy

For more information visit www.lumouslighting.com or call +358 29 310 310

Subject to change without prior notice.

